



GrilleGuy.com, LLC

2005 – 2006 Legacy GT, Outback Grille Install Instructions



BEFORE



AFTER

Package Contents:

1 Grille
6 Nylon tie wraps
designated length of edging material

Tools Required (grille installation only):

Wire cutters
Phillips head screwdriver
Hacksaw blade or dremel tool (hacksaw blade works better – less melting)

Note:

GrilleGuy.com, LLC was only granted access to an OEM grille that was removed by the customer and shipped to our location. For this reason, we cannot provide detailed information on how to remove and reinstall the OEM grille or the Subaru emblem. We suggest visiting the LegacyGT forum (www.LegacyGT.com) if you feel you need detailed information.

Our grille instructions will follow on the next pages. We assume you have removed the grille from the car and the Subaru emblem from the grille.



GrilleGuy.com, LLC



1. Remove the Chrome "wings" using a Phillips head screwdriver. These will not be reused.

2. Using a hacksaw blade, a dremel tool, or other cutting device – remove the raised emblem mount. Be sure not to cut the web that connects to the bottom of the grille, this would weaken the grille frame.



3. We found it much easier to cut one side at a time, We did the top then the bottom.

4. You can use some sandpaper afterwards to knock off any debris and smooth the edges; however, it is not a necessary step.



5. The grille is mounted to the OEM grille via the 4 nylon tie wraps. I placed 1 at each end (right at the angle) and then 2 in the center 1 at the bottom and 1 at the top. If you look very closely, you can see 3 of them in this photo. The tie wraps simply loop around the wing and or vertical fins. Do NOT over tighten the tie wraps. Also

place them in holes that are closest to the edging so that they are blend into the trim. The grille can now be reinstalled in the vehicle.